

Slim Panel PC

Fanless Operation solution



SPECIFICATIONS

Model Name	CP/SPC H150 & CP/SPC H170
Main Board	
CPU	Onboard ULV VIA Eden™ 1.0GHz Processor
Memory	1 x 200 Pin SODIMM socket up to 1GB DDR2 SDRAM
Chipset	VIA CX700M
Graphics	-VIA CX700M with integrated 2D and 3D Graphics engine supporting MPEG-4 accelerator, MPEG-2 decoder and WMV9 video acceleration, shared system memory max. 128MB
Network	2 x Dual Realtek RTL8101L Gigabit Ethernet 802.11g Wireless Lan (optional)
Audio	Realtek ALC883 HD Codec ,support Line-Out and Mic
Power Supply	DC-IN power adapter (64W Max.)
OS	Windows XP/XPE/Vista/WEPOS/POSReady 2009
LED	Power, HDD
Display	
LCD	15" / 17" LCD
Max. Resolution	15" : 1024 x 768 / 17" : 1280 x 1024
Brightness	15" : 250 cd/m ² / 17" : 300 cd/m ²
Touch Screen	5-wire Analog resistive (HIGGSTECH, E-Turbo)
Storage	
HDD	1 x 2.5" SATA hard disk drive
I/O Ports	
USB	4 x USB 2.0 (2 x Rear I/O, 1 x pin header for touch control board and 1 x for reserved)
Serial Ports	2 x DB-9 (rear I/O)
LAN	2 x RJ-45 interface
PS/2	1 x PS/2 ports (for keyboard and mouse)
Audio	Internal 2W speaker x 2, 1 x Mic In
Printer	N/A
CF Socket	YES
Physical dimensions	
Weight	TBD
Dimension	TBD
Environment	
EMC & Safety	CE, FCC
Temperature	Operating: 0 ~ 40°C Storage: -20 ~ 60°C
Humidity	10% ~ 90%
Optional Items	
DRAM Module	DDR2-667 512MB, 1GB (200pin) SODIMM
HDD	80GB (2.5",SATA, 5400RPM) or SSD
CompactFlash Card	1GB ~ 16GB
1 of the 2 optional (W-LAN or MSR)	W-LAN: 802.11g Wireless LAN module MSR: USB Type Track 1/2/3 Magnetic Stripe Reader
OS	Windows XP/XPE/Vista/WEPOS/POSReady 2009

* ATOM coming soon

* The specification is subject to change without any prior notice.